







Battery Pack **BTR series**

	BTR-09A	BTR-10	BTR-11	BTR-11A	BTR-15		BTR-12A
Photo						Photo	
Battery charger	ADC-18	-	-	-	-	Battery charger	-
Battery charge cord	DCC-18	-	-	-	-	Battery charge cord	-
AC adaptor for charger	-	ADC-19A	ADC-19A	ADC-19A	ADC-20	AC adaptor for charger	ADC-09A
AC power cord for charger	-	ACC-08,09,10,11, or12	ACC-08,09,10,11, or12	ACC-08,09,10,11, or12	ACC-14,15,16, or17	AC power cord for charger	ACC-08,09,10,11, or12
Type	Li-ion (Lithium-ion)	Li-ion (Lithium-ion)	Li-ion (Lithium-ion)	Li-ion (Lithium-ion)	Li-ion (Lithium-ion)	Type	Li-ion (Lithium-ion)
Use for (No. of splicer operation) *Splicing/ tube heating	70S,70S+ (200 cycles)	12S (100 cycles)	22S (200 cycles)	41S (200 cycles)	90S (300 cycles)	Battery capacity(Numbe r of jacket stripping)	RS03 (600 times at Eco mode)
	70R,70R+ (110 cycles)	12R (100 cycles)	21S (200 cycles)	-	90R16 (130 cycles)		-
	19S,19S+ (180 cycles)	-	-	-	90R12 (165cycles)		-
	19R,19R+ (140 cycles)	-	-	-	90R4 (210 cycles)		-

Go to the next page

	BTR-09	BTR-10	BTR-11	BTR-11A	BTR-15		BTR-12A
Photo						Photo	
Output voltage	14.4V	14.8V	14.4V	14.4V	14.4V	Output voltage	7.2V
Battery capacity	4.0Ah	2.0Ah	3.4Ah	3.4Ah	6.4Ah	Battery capacity	1.8Ah
Expected battery cycle life	Max. 500 cycles	Max. 500 cycles	Max. 500 cycles	Max. 500 cycles	Max. 500 cycles	Expected battery cycle life	Max. 500 cycles
Battery capacity indicator	Available with 4-step LED	Available with monitor of the splicer	Available with monitor of the splicer	Available with monitor of the splicer	Available with 4-step LED	Battery capacity indicator	Available with monitor of the splicer
Operating condition	-10 to +50 degree C/ 0 to 95%RH non-condensing					Operating condition	-10 to +50 degree C/ 0 to 95%RH non-condensing
Dimension	132W x 117D x 38Hmm	108W x 69D x 11Hmm	83W x 66D x 19Hmm	83W x 66D x 19Hmm	148W x 125D x 23Hmm	Dimension	58W x 48D x 21Hmm
Weight	0.56kg	0.17kg	0.20kg	0.20kg	0.57kg	Weight	0.08kg

Specifications and descriptions are subject to change without prior notice. © 2015 Fujikura Ltd.

Fujikura Ltd.

1-5-1, Kiba, Koto-ku, Tokyo 135-8512, Japan
 General inquiries : +81-3-5606-1164
 Service & support : +81-43-484-3962 <https://www.fujikura.com>

Fujikura Asia Ltd.

438A Alexandra Road, Block A Alexandra Technopark #08-03 Singapore 119967
 General inquiries, Service & support : +65-6-278-8955
<https://www.fujikura.com.sg>

Fujikura Europe Ltd.

C51 Barwell Business Park, Leatherhead Road, Chessington, Surrey KT9 2NY,
 General inquiries : +44-20-8240-2000
 Service & support : +44-20-8240-2020 <https://www.fujikura.co.uk>

AFL

260, Parkway East, Duncan, SC29334, USA
 General inquiries : +1-800-235-3423
 Service & support : +1-800-866-3602 <https://www.aflglobal.com>

Fujikura (China) Co., Ltd.

7th Floor, Shanghai Hang Seng Bank Tower, 1000 Lujiazui Ring Road, Pudong New Area, Shanghai 200120, CHINA
 General inquiries, service & support : +86-21-6841-3636 <http://www.fujikura.com.cn>