

JETTING MICRO DUCT LUBE

MICRO DUCT LUBE is a special lubricant for ducts up to 12 mm inside diameter, used previous to blowing of mini/micro fibre/cables.

MICRO DUCT LUBE is water based and can be used down to -15 degrees C. It leaves a very tiny film of lubricant, reduces drastically the friction, static electricity, and adheres perfectly to the fibre/cable and to the duct surface.

Use:

1. Clean the inside of the duct by blowing a sponge slowly thru the duct.
2. Shake the bottle before using.
3. Pre lubricate by:
 - Place a sponge as far into the duct according to the table on the bottle.
 - Fill the suggested lubricant into the duct.
 - Place one or two sponges in the end and blow this thru slowly.
 - For best result, leave the lubricate to dry for 5- 10 min
4. The duct is now ready for fibre / cable blowing.

Quantities:

15 ml x 1.000 mt for diameter 12 mm (about 15 cm full Duct)

10 ml x 1.000 mt for diameter 8 mm (about 20 cm full Duct)

5 ml x 1.000 mt for diameter 4 mm (about 30 cm full Duct)

Technical Specifications:

| | |
|-------------------|-------------------------------------|
| Aspect | White liquid tiny viscosity |
| Odour | characteristic |
| Viscosity | 30 sec. Ford cup diam. mm 4 at 20C° |
| Specific gravity | 1,030 +- 0,03 gr/cm ³ |
| pH | 7,5 +- 0,5 |
| Inflammability | non infiammabile |
| Temperature | -15° + 70° C. |
| Biodegradability | yes |
| Toxic | The product is not toxic. |
| HS Code | 3403.9900 |
| Country of origin | Italy |
| Art. No | 34030 |