



USB Headsets - Designed for Music & Speech

COMMANDER
BY JPL



Commander USB

Universal 'Plug & Play' USB professional office and contact centre headset, compatible with all major softphones. Premium audio speakers designed for music and speech, ideal for users moving to PC telephony for webinars, conference calls, music and other multimedia applications.



telecroatian network
www.telecron.net



telecroatian network
www.telecron.net




In-line Control Features

3 button in-line control with volume and mute
'Plug & Play' solution - No software download needed

User will know the buttons by feel as each button will feel different

Ribbing on the side of the control box to indicate the direction of the buttons

Red LED illumination when mute is in-use



USB-A / USB-C ADAPTER



LEATHERETTE CUSHION



SOFT SHELL CARRY CASE

Overview

Features	Left / right speaker side compatible
	Premium audio speakers designed for music and speech
	Surround Shield™ noise cancelling microphone
	Compatible with internet calling via USB-A or USB-C connection
	Fully flexible microphone for exact positioning
	270° adjustable microphone boom
	'Put and stay' ratchet microphone boom arm
	Swivel T-bar with soft feel padded leatherette cushion
	Overhead, sure-fit fully adjustable headband
What's included	Headset fitted with 60mm leatherette ear cushions, USB-A / USB-C direct plug-in, quick start guide and soft shell headset carry case
Headset Weight	~ 62g / ~ 82g
Connection	USB-A / USB-C direct plug-in
Certifications	UKCA, CE, FCC, RoHS, REACH
Warranty	2 Years repair or replacement warranty
MOQ	Master Shipping Carton: 40
EAN:	Commander-1: 5060126959007, Commander-2: 5060126959021
SKU:	Commander-1: 575-344-003, Commander-2: 575-344-004

Technical Data

Microphone:

Directivity:	Unidirectional
Impedance:	1.0kΩ
Sensitivity:	-49±3dB (0dB=1V/Pa)
Frequency Range:	100-16,000Hz
Operating Temp:	-20°C~+60°C
Storage Temp:	-25°C~+70°C

Speaker:

Size:	ø30 mm
Input Power:	50 mW (1.26V)
Max Power:	100 mW (1.79V)
Impedance:	32Ω ±10% at 1kHz, 0.18V
Sound Pressure:	122±3dB at 1kHz
Resonance Frequency:	150±30 (20%) Hz
Frequency Range:	20Hz ~ 20,000Hz
Operating Temp:	-25°C ~ +50°C
Storage Temp:	-25°C ~ +50°C

